



S800 Countertop Payment Terminal

- Contactless, Chip, Magstripe
- Visa & MasterCard NFC
- 3G, GPRS, WiFi, LAN, PSTN
- Large Colour Display
- PCI PTS 3.x, SRED
- High Speed Printer
- Linux OS

PAX's S800 is the world's most innovative countertop payment terminal powered by a secure operating platform. This supports rapid development of customized and secure software applications that give new meaning to the concept of payment and value-added services.

The S800 comes in a compact and stylish form factor, equipped with large colour screen, wide choice of connectivity options and built-in contactless capability. The S800 packs a 32-bit ARM11 processor and massive amounts of memory to deliver exceptional performance.

Your Payment Partner of Choice



S800 Countertop Payment Terminal

Features & Benefits



High Reliability & Exceptional Stability

- Sleek compact design
- Built-in contactless reader
- Fast thermal printer (30 lps)
- Multiple peripheral ports
- Advanced DDR technology
- 400MHz 32-bit ARM11 processor
- GPRS / Ethernet / WiFi / PSTN / 3G (WCDMA)

Unprecedented Security

- PCI PTS 3.x certified, SRED
- Supports HASH function
- Supports RSA, AES, 3DES
- Supports DUKPT, MK/SK, FIXED KEY
- Secure key embedded area

Open & Flexible Operating System

- Secure & flexible platform
- Easy software application development
- User-friendly interface with powerful GUI
- Multi-tasking OS maintains application integrity
- Plug-and-Play to extend functionality on-site

Multimedia Performance

- Loudspeaker
- Large colour screen display
- Supports HD images and video

Specifications

Processor

32-bit ARM11

Memory

192MB standard (128MB Flash, 64MB DDR)
Micro SD (TF card) up to 32GB

Display

2.8 inch 320 x 240 pixels TFT colour LCD

Keypad

10 numeric / letter keys, 7 function keys
Back-lighting

Printer

Thermal printer, Speed: 30 lines per second
or faster depending on font size
Paper roll width / diameter: 58mm / 50mm

Card Slots

3 SAMs
or 2SAMs, 1 SIM
or 1 SAM, Dual SIM

Magnetic Card Reader

Track 1/2/3, bi-directional

Smart Card Reader

EMV L1 & L2

Contactless Card Reader

MasterCard Contactless & Visa payWave
American Express ExpressPay
Discover DPAS
ISO/IEC 14443 Type A/B
Mifare®, Felica, NFC

Audio

Speaker, 90dB

Communication

Modem: Sync. (HDLC up to 9600bps);
Async. (V.92, up to 56Kbps)
Ethernet (optional)
WiFi (optional)
GPRS/ 3G (WCDMA) (optional)

Peripheral Ports

1 x RS232, 1 x RS232 / Ethernet
1 x PINpad, 1 x Line, 2 x Mini USB

Security

DUKPT, Master/Session, 3DES,
ANSI/ISO9564 format 0, 1,3
PIN ciphered key algorithm
ANSI X 9.9/X9.19 MAC algorithm

Environmental

0°C to 50°C (32°F to 122°F) operating temperature
10% to 93% relative humidity, non-condensing
-20°C to 70°C (-4°F to 158°F) storage temperature

Voltage

Input: 100~240VAC, 50Hz/60Hz, 1A
Output: 9VDC, 1A

Physical

Length: 203mm
Width: 86mm
Height: 70mm

Weight

454g

Certifications

PCI PTS 3.x, SRED
EMV Contact L1 & L2
EMV Contactless L1
Visa payWave
MasterCard Contactless
AMEX Expresspay
JCB J/Speedy
MasterCard TQM

www.pax.com.cn

This document is provided to you for informational purposes only. All features and specifications are subject to change without notice.
PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries.
All other trademarks or brand names are the properties of their respective holders. Copyright 2015, PAX Technology Limited, All Rights Reserved.


PAX
Your Payment Partner of Choice