



# D210 Mobile Payment Terminal

- **Contactless, Chip, Magstripe**
- **3G, GPRS, Bluetooth, WiFi**
- **iOS & Android Compatible**
- **Visa & MasterCard NFC**
- **PCI PTS 4.x Certified**
- **Apple MFi Approved**

PAX's D210 is a compact mobile payment device designed to interact with customers. Supporting Bluetooth, WiFi, GPRS, 3G (WCDMA) or cable connection, the D210 connects to a wide range of existing and new smart devices to keep up with an emerging marketplace. Apple Inc. has given the D210 a special certification called MFi meaning that Apple has tested and approved the D210 to meet the highest performance standards for integration with any iPad or iPhone.

*Your Payment Partner of Choice*



# D210 Mobile Payment Terminal

## Features & Benefits



### High Reliability & Exceptional Performance

- Smart card, magstripe & contactless enabled
- Stylishly designed for comfort and convenience
- Contactless card reader supporting NFC  
2.8 inch colour screen
- Large memory capacity

### Unprecedented Security

- PCI PTS 4.x approved
- Secure key embedded area

### Perfect Expansibility

- Open and flexible OS for customized value-added services
- Supports WiFi, Bluetooth, GPRS and 3G (WCDMA)

## Specifications

### Processor

32-bit ARM 11

### Memory

192MB (128MB Flash, 64MB SDRAM)  
Micro SD (TF card) up to 32GB

### Display

2.8 inch TFT color LCD, 320 x 240 pixels  
e-signature (optional)

### Printer

High-speed thermal printer, speed: 30 lps  
Paper roll width / diameter : 58mm / 40mm

### Keypad

10 numeric & 8 function keys

### Magnetic card reader

Track1 / 2 / 3, Bi-directional

### Smart Card Reader

EMV L1 & L2 certified

### Contactless Card Reader

MasterCard Contactless & Visa payWave  
ISO14443 Type A/B  
Mifare®, Felica, NFC

### Communication

Bluetooth 4.0 / WiFi / GPRS  
3G (WCDMA) (optional)

### Card slots

2 SAMs, 1 SIM  
or 1 SAM, Dual SIM

### Peripheral Ports

1 x Mini USB (OTG), 1 x Mini USB (RS232)  
1 x Power port

### Security

PCI PTS 4.x certified

### Environmental

0°C to 50°C (32°F to 122°F) operating temperature  
-20°C to 70°C (-4°F to 158°F) storage temperature  
10% to 93% relative humidity, non-condensing

### Voltage

Battery, 7.4V, 2300mAh  
Input: 100 - 240V AC, 50 / 60 Hz, 0.3A  
Output: 9VDC, 1A

### Physical

Length: 162.5mm  
Width: 80mm  
Height: 56mm

### Weight

360g with battery

### Accessories

Adapter  
Charging Base (optional)

### Certifications

PCI PTS 4.x, SRED  
EMV Contact L1 & L2  
EMV Contactless L1  
Visa payWave  
MasterCard Contactless  
AMEX Expresspay  
Discover D-PAS  
MasterCard TQM